



MINO 60 CIRCLE 1500

suspended DIRECT

034-221051DH

PROJECT

TYPE

NOTES

QUANTITY

DATE

GENERAL

Ceiling
Suspended
dark gray
2540 lm/m
IP20
10800 lm
RAL7022^a
Extended Configuration

LED

3000 K
CRI ≥ 80
L80 / 50000 h
initial ≤ 3 MacAdam

OPTICAL

High Performance Opal


PHYSICAL

Cable 1500 mm
diameter 1560 mm
width 60 mm
height 80 mm
centerline radius 750 mm

ELECTRICAL

non DIM
110 W
PC1 220-240V
25 W/m

^a RAL Palette colors may deviate slightly due to production conditions.



Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; surface powder coated in white, grey, dark grey, black, beige or dark brown; lighting insert consisting of highly reflective coated die-cast aluminium for improved thermal management; Suspended luminaire with 1500mm cable suspension; with integrated tool-less suspension height adjustment; incl. transparent feed; HPO (High Performance Opal) cover for uniform illumination; with increased transmission and diffusion; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; optional with direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering; binning initial ≤ 3 MacAdam; available in the light colours 3000K and 4000K; CRI ≥ 80; min. 90% of the luminous flux after 50000 hours; degree of protection IP 20; PC I; optionally non-dimmable or DALI dimmable

Light Distribution

