



VELA EVO 1200 ceiling DIRECT

073-118051DO

DATE	_____
PROJECT	_____
REMARK	_____
TYPE	_____
QUANTITY	_____

Quickinfo

GENERAL

Ceiling _____
 Surface _____
 dark gray _____
 RAL7022 ^a _____
 8970 lm _____
 IP40 _____
 Extended Configuration _____

LED

3000 K _____
 CRI ≥ 80 _____
 L80 / 50000 h _____
 initial ≤ 3 MacAdam _____

OPTICAL

Opal _____
 ≥65° <3000 cd/m² _____

PHYSICAL

diameter 1200 mm _____
 height 92 mm _____
 20.0 kg _____

ELECTRICAL

81 W _____
 non DIM _____
 111 lm/W _____

^a RAL Palette colors may deviate slightly due to production conditions.



Round luminaire housing in aluminium, rolled profile, seamlessly welded; surface powder coated in white, grey, dark grey, black, beige or dark brown; highly reflective coating for improved efficiency; convenient quick mounting system without tools; completely homogeneously illuminated, satinised PMMA cover; up to ø600mm: microprismatic PMMA cover; workplace light suitable for VDUs according to DIN EN 12464-1 (UGR < 19); direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; same light density for all surface lights with the same components (e LED, e² LED or e2+ LED); energy-efficient LEDs with very good colour rendering; binning initial ≤ 3 MacAdam; available in the light colours 3000K and 4000K; CRI ≥ 80; min. 90% of the luminous flux after 50000 hours; luminaire with 2 cable openings and plug-in terminals for through wiring; protection class IP 40; PC I; DALI dimmable with CLO function; optional non-dimmable

Light Distribution

