



# VELA EVO 1200 ceiling DIRECT

073-118051DO

PROJECT

TYPE

NOTES

QUANTITY

DATE

## GENERAL

Ceiling  
Surface  
dark grey  
IP40  
8970 lm  
RAL7022<sup>a</sup>  
Extended Configuration

## LED

3000 K  
CRI ≥ 80  
L80 / 50000 h  
initial ≤ 3 MacAdam  
MR 0.54  
MDER 0.49

## OPTICAL

Opal  
≥65° <3000 cd/m<sup>2</sup>


## PHYSICAL

diameter 1200 mm  
height 92 mm  
20 kg

## ELECTRICAL

non DIM  
81 W  
111 lm/W  
PC1 220-240V

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.



## Product family description

Round luminaire housing in aluminium, rolled profile, seamlessly welded; surface powder coated in white, grey, dark grey, black, beige or dark brown; highly reflective coating for improved efficiency; convenient quick mounting system without tools; completely homogeneously illuminated, satinised PMMA cover; up to ø600mm: microprismatic PMMA cover; workplace light suitable for VDUs according to DIN EN 12464-1 (UGR < 19); direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; same light density for all surface lights with the same components (e LED, e<sup>2</sup> LED or e2+ LED); energy-efficient LEDs with very good colour rendering; binning initial ≤ 3 MacAdam; available in the light colours 3000K and 4000K; CRI ≥ 80; min. 90% of the luminous flux after 50000 hours; luminaire with 2 cable openings and plug-in terminals for through wiring; degree of protection IP 40; PC I; DALI dimmable with CLO function; optional non-dimmable

## Light Distribution

