



# VELA EVO 1200 ceiling DIRECT

073-118051DO

PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

## Quickinfo

### GENERAL

Ceiling \_\_\_\_\_  
 Surface \_\_\_\_\_  
 dark gray \_\_\_\_\_  
 RAL7022 <sup>a</sup> \_\_\_\_\_  
 8970 lm \_\_\_\_\_  
 IP40 \_\_\_\_\_  
 Extended Configuration \_\_\_\_\_

### LED

3000 K \_\_\_\_\_  
 CRI ≥ 80 \_\_\_\_\_  
 L80 / 50000 h \_\_\_\_\_  
 initial ≤ 3 MacAdam \_\_\_\_\_

### OPTICAL

Opal \_\_\_\_\_  
 ≥65° <3000 cd/m<sup>2</sup> \_\_\_\_\_

### PHYSICAL

diameter 1200 mm \_\_\_\_\_  
 height 92 mm \_\_\_\_\_  
 20.0 kg \_\_\_\_\_

### ELECTRICAL

81 W \_\_\_\_\_  
 non DIM \_\_\_\_\_  
 111 lm/W \_\_\_\_\_  
 PC1 220-240V \_\_\_\_\_

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.



Round luminaire housing in aluminium, rolled profile, seamlessly welded; surface powder coated in white, grey, dark grey, black, beige or dark brown; highly reflective coating for improved efficiency; convenient quick mounting system without tools; completely homogeneously illuminated, satinised PMMA cover; up to ø600mm: microprismatic PMMA cover; workplace light suitable for VDUs according to DIN EN 12464-1 (UGR < 19); direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; same light density for all surface lights with the same components (e LED, e<sup>2</sup> LED or e2+ LED); energy-efficient LEDs with very good colour rendering; binning initial ≤ 3 MacAdam; available in the light colours 3000K and 4000K; CRI ≥ 80; min. 90% of the luminous flux after 50000 hours; luminaire with 2 cable openings and plug-in terminals for through wiring; degree of protection IP 40; PC I; DALI dimmable with CLO function; optional non-dimmable

## Light Distribution

